

# GB-Annealed IronWire™



Grytgöls Bruk has a wide range of iron wire. Our iron wire can be supplied with different processing methods, coatings and delivery forms. GB-Annealed IronWire™ is available with copper-, zinc- or non coating, dry- or wet drawn. Our delivery covers all forms of commercially available standards both in terms of weight as different with different spool types. Our flexible manufacturing process also makes it possible to customize GB-Annealed IronWire™ to the specific conditions that each individual customer requires.

Like our other products, GB-Annealed IronWire™ is characterized by a high quality layer (copper-, zinc- or none coated), tight dimensional tolerances and absolute purity, resulting in a precise and reliable wire feeding for all kinds of stitching.

GB-Annealed IronWire™ is manufactured at our plant in Grytgöl, Sweden, and here we have used our extensive experience in the wire know-how to provide a product with unique features. Our specially developed manufacturing process ensures that you will get a product with stringent quality standards, which means that GB-Annealed IronWire™ always shows the same excellent features.









**SE-610 11 Grytgöl, Sverige**  
**Telefon: 0122 622 60 • Fax: 0122 433 63**  
**E-Mail: [wire@grytgol.com](mailto:wire@grytgol.com) • Hemsida: [www.grytgol.com](http://www.grytgol.com)**

**Delivery forms:**

GB-Annealed IronWire™ is available with copper-, zinc- or none coating, dry- or wet drawn. Our delivery also covers all forms of commercially available standards both in terms of weight as different with different spool types. If you have specific requirements, we also have the possibility to customize the wire according to your needs.

Below you will find example of our delivery forms.

		
GB-Annealed IronWire™ Copper coated CO300	GB-Annealed IronWire™ Copper coated A1000	GB-Annealed IronWire™ Copper coated Ring
		
GB-Annealed IronWire™ Zinc coated CO300	GB-Annealed IronWire™ None coated A1000	GB- Annealed IronWire™ None coated S1000

Type of spool	Weight (kg)	Tap diameter Ød (mm)	Flange/Diameter ØD (mm)	Width/Height H (mm)	Spool material	Number of spools per pallet
CO300	300	35	760	280	Sheet material	1
A1000	1000	560	870	430		1
Ring	30-90					
S1000	1000	130	850	465	Steel	1

**Dimension:**

GB-Annealed IronWire™ can be delivered in wire diameters 0,60-4,00 (mm).

**Coating:**

GB-Annealed IronWire™ can be supplied with copper-, zinc- or none coated, and in dry –or wet drawn condition.

**Quality:**

Grytgöls Bruk is certified according to SS-EN ISO 9001:2008.



**SE-610 11 Grytgöl, Sverige**  
**Telefon: 0122 622 60 • Fax: 0122 433 63**  
**E-Mail: [wire@grytgol.com](mailto:wire@grytgol.com) • Hemsida: [www.grytgol.com](http://www.grytgol.com)**