

# GB-BoxStitchingWire™



GB-BoxStitchingWire™ is a flat rolled stitching wire which is specially developed to cope with today's tough requirements for rapid and continuous operation for stapling various corrugated cartons. GB-BoxStitchingWire™ is available with a surface layer of both copper and zinc, and no matter what type you choose GB-BoxStitchingWire™ always exhibits the same excellent features.

GB-BoxStitchingWire™ works very well in any stitching machines on the market. Our delivery forms cover all available standards, in terms of weight, dimensions and different kind of spool sizes. Our flexible manufacturing process also makes it possible to customize GB-BoxStitchingWire™ to the specific characteristics of each individual customer.

Like our other products, GB-BoxStitchingWire™ is characterized by a high quality layer (copper or zinc), tight dimensional tolerances and absolute purity, resulting in a precise and reliable wire feeding for all kinds of stitching.

GB-BoxStitchingWire™ is manufactured at our plant in Grytgöl, Sweden, and here we have used our extensive experience in the wire know-how to provide a product with unique features. Our specially developed manufacturing process ensures a product with stringent quality standards, which means that GB-BoxStitchingWire™ always has the same excellent features.



**Grytgöls Bruk AB**







**SE-610 11 Grytgöl, Sweden**


**Phone: +46 122 622 60 • Fax: +46 122 433 63**

**E-Mail: [wire@grytgol.com](mailto:wire@grytgol.com) • Web page: [www.grytgol.com](http://www.grytgol.com)**

**Product information.**

Our flexible manufacturing process makes it possible to customize GB-BoxStitchingWire™ to the specific characteristics of each individual customer in terms of dimensions, type of spools, and coating. A selection of our delivery forms can be found below.

						
C4		K4		K8		
						
K11		K20				
Spool	Weight (kg)	Tap hole Ød (mm)	Flange ØD (mm)	Width H (mm)	Spool material	Pcs/pallet
C4	Ca 4	18	155	61,5	Plastic	5/box - 48 boxes/pallet
K4	Ca 4	67	180	52	Plastic	5/box - 40 boxes/pallet
K8	8	67	226	52	Plastic	2/box - 60 boxes/pallet
K11	11	67	225	60	Plastic	2/box - 48 boxes/pallet
K20	17	98	240	95	Plastic	60



**Dimensions:**

All type of spools can be delivered in a variety of dimensions in the range of 1.00 to 3.50 mm (width) and 0.40 to 1.50 mm (thickness), below are some examples of our standard sizes (mm) that we keep in stock.

1,20*0,70	2,00*0,70	2,25*0,75	2,50*0,50	2,50*0,60	2,60*0,50	2,60*0,60	3,00*0,50
-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------

**Coating:**

All type of spools and dimensions can be delivered with copper- or zinc coating.

**Quality:**

Grytgöls Bruk is certified according to SS-EN ISO 9001:2008.



**Grytgöls Bruk AB**

**SE-610 11 Grytgöl, Sweden**  
**Phone: +46 122 622 60 • Fax: +46 122 433 63**  
**E-Mail: [wire@grytgol.com](mailto:wire@grytgol.com) • Web page: [www.grytgol.com](http://www.grytgol.com)**