


GB-CrownWire™



GB-CrownWire™ is a galvanized stitching wire that has been specially developed to meet today's tough requirements in all types of fast, continuous stitching processes.

GB-CrownWire™ is highly compatible with all stitching equipment currently on the market. For applications with special requirements concerning the thickness of material to be stitched, GB-CrownWire™ can also be supplied in the form, specially designed for that kind of stitching, GB-CrownWire-Power™. GB-CrownWire™ is available in a range of different spool types and wire dimensions to suit a variety of needs.

GB-Crown Wire™ is manufactured at our plant in Grytgöl, Sweden, and here we have used our extensive experience in the wire know-how to provide a product with unique features. Our specially developed manufacturing process ensures a product with stringent quality standards, which means that GB-Crown Wire™ always has the same excellent features.



Grytgöls Bruk AB


SE-610 11 Grytgöl, Sweden

Phone: +46 122 622 60 • Fax: +46 122 433 63

E-Mail: wire@grytgol.com • Web page: www.grytgol.com

Product information**Packaging:**

Spool	Weight (kg/lbs)	Tap hole Ød (mm/inch)	Flange ØD (mm/inch)	Width H (mm/inch)	Spool material	Pcs/pallet
H3	Aprox. 3/6,6	17/0,67	147/5,79	50/1,97	Plastic	8 / box
H6	Aprox. 6/13,2	17/0,67	150/5,90	100/3,94	Plastic	4 / box
H11	Aprox. 11/24,3	46/1,81	200/7,87	124/4,88	Plastic	100
CO20	Aprox. 20/44,1	52/2,05	300/11,81	100/3,94	Plastic	50
H21/47	Aprox. 21/46,3	32/1,26	205/8,07	177/6,97	Plastic	45
H30	Aprox. 30/66,1	32/1,26	250/9,84	166/6,54	Wood	36
H50	Aprox. 45	35/1,38	355/13,98	200/7,87	Plastic	24
H100	Aprox. 85	127/5,00	355/13,98	355/13,98	Plastic	12

**Dimensions:**

All spools can be delivered in the following dimensions (mm/inch)

0,45/0,018	0,50/0,020	0,55/0,022	0,60/0,024	0,67/0,026	0,70/0,028	0,75/0,030	0,80/0,032
------------	------------	------------	------------	------------	------------	------------	------------

Mechanical properties:

	GB CrownWire™	GB CrownWire-Power™
Tensile strength (N/mm ² /PSI)	Aprox. 900/130 000	Aprox. 1200/170 000

Quality:

Grytgöls Bruk is certified according to SS-EN ISO 9001:2008.



Grytgöls Bruk AB

SE-610 11 Grytgöl, Sweden

Phone: +46 122 622 60 • Fax: +46 122 433 63

E-Mail: wire@grytgol.com • Web page: www.grytgol.com