

GB-IronWire™



Grytgöls Bruk has a wide range of iron wire. Our iron wire can be supplied with different processing methods, coatings and delivery forms. GB-IronWire™ is available with copper-, zinc- or non coating, dry- or wet drawn. Our delivery covers all forms of commercially available standards both in terms of weight as different with different spool types. Our flexible manufacturing process also makes it possible to customize GB-IronWire™ to the specific conditions that each individual customer requires.

Like our other products, GB-IronWire™ is characterized by a high quality layer (copper-, zinc- or none coated), tight dimensional tolerances and absolute purity, resulting in a precise and reliable wire feeding for all kinds of stitching.

GB-IronWire™ is manufactured at our plant in Grytgöl, Sweden, and here we have used our extensive experience in the wire know-how to provide a product with unique features. Our specially developed manufacturing process ensures that you will get a product with stringent quality standards, which means that GB-IronWire™ always shows the same excellent features.



SE-610 11 Grytgöl, Sweden
Phone: +46 122 622 60 • Fax: +46 122 433 63
E-Mail: wire@grytgol.com • Web page: www.grytgol.com

Delivery forms:

GB-IronWire™ is available with copper-, zinc- or none coating, dry- or wet drawn. Our delivery also covers all forms of commercially available standards both in terms of weight as different with different spool types. If you have specific requirements, we also have the possibility to customize the wire according to your needs. Below you will find example of our delivery forms.

						
GB-IronWire™ Copper coated CO300		GB-IronWire™ Copper coated A1000		GB-IronWire™ Copper coated Ring		
						
GB-IronWire™ Copper coated W250/60		GB-IronWire™ None coated H50		GB-IronWire™ Zinc coated S1000		
Type of spool	Weight (kg)	Tap diameter Ød (mm)	Flange/Diameter ØD (mm)	Width/Height H (mm)	Spool material	Number of spools per pallet
CO300	300	35	760	280	Sheet material	1
A1000	1000	560	870	430		1
Ring	30-90					
W250	250		520	830	Corrugated	4
W60	60		520	430	Corrugated	4
H50	45	35	355	200	Plastic	24
S1000	1000	130	850	465	Steel	1

Dimension:

GB-IronWire™ can be delivered in wire diameters 0,60-4,00 (mm).

Coating:

GB-IronWire™ can be supplied with copper-, zinc- or none coated, and in dry –or wet drawn condition.

Quality:

Grytgöls Bruk is certified according to SS-EN ISO 9001:2008.



SE-610 11 Grytgöl, Sweden
 Phone: +46 122 622 60 • Fax: +46 122 433 63
 E-Mail: wire@grytgol.com • Web page: www.grytgol.com